



# THE 880F4 SERIES



## 880F4 A GREAT SAW WITH A BAD ATTITUDE

The new 880F4 cutting system offers the superior strength of FORCE4™ technology in a package that meets industry standards of design and ergonomics. Built for the hardcore cutter, this sleek powerhouse is packed with features designed to make it the hardest working saw ICS® has ever made.

### SAW SELECTION

In addition to cutting depth and power requirements, estimated frequency of use is important when selecting a saw. Use the chart below to determine the right saw for your cutting needs.



### 880F4 PRODUCT SPECIFICATIONS - 8 GPM

<b>WEIGHT</b>	27.3 lbs (12.4 kg) with 15-inch (38 cm) bar and chain
<b>BAR LENGTH</b>	Up to 25 in (63 cm)
<b>MOTOR SPEED</b>	6100 rpm
<b>POWERHEAD DIMENSIONS</b>	23 in (58.5 cm) length 10.5 in (26.5 cm) height 9.5 in (24 cm) width
<b>TORQUE</b>	122 in-lbs (13.8 Nm)
<b>HORSEPOWER</b>	11.5 hp (8.6 kW)
<b>HYDRAULIC SUPPLY</b>	8 gpm (30 lpm), 2500 psi (172.5 bar)
<b>NOISE LEVEL</b>	88 dB @ 3 ft (1 m)
<b>VIBRATION LEVEL</b>	4 meters/second <sup>2</sup> (front handle)
<b>WATER SUPPLY</b>	Minimum 20 psi (1.5 bar)

*• Product data shown is rated based on maximum input conditions and efficiency assumptions and may vary dependent on power supply.*

### 880F4 PRODUCT SPECIFICATIONS - 12 GPM

<b>WEIGHT</b>	27.3 lbs (12.4 kg) with 15-inch (38 cm) bar and chain
<b>BAR LENGTH</b>	Up to 25 in (63 cm)
<b>MOTOR SPEED</b>	6400 rpm
<b>POWERHEAD DIMENSIONS</b>	23 in (58.5 cm) length 10.5 in (26.5 cm) height 9.5 in (24 cm) width
<b>TORQUE</b>	172 in-lbs (19.5 Nm)
<b>HORSEPOWER</b>	17.5 hp (13 kW)
<b>HYDRAULIC SUPPLY</b>	12 gpm (45 lpm), 2500 psi (172.5 bar)
<b>NOISE LEVEL</b>	88 dB @ 3 ft (1 m)
<b>VIBRATION LEVEL</b>	4 meters/second <sup>2</sup> (front handle)
<b>WATER SUPPLY</b>	Minimum 20 psi (1.5 bar)

*• Product data shown is rated based on maximum input conditions and efficiency assumptions and may vary dependent on power supply.*



[icsbestway.com](http://icsbestway.com)

ICS | Blount Inc. • 4909 SE International Way Portland, OR 97222 USA • Ph 800.321.1240 • Fax 503.653.4393

Copyright 2011 ICS | Blount Inc. Pricing and specifications subject to change without notice. All rights reserved. ICS, WallWalker, SpeedHook, SealPRO and PowerGrit are registered trademarks of ICS. The best way to cut concrete, DCT, TSS, ProFORCE, TwinMAX and FORCE4 are trademarks of ICS. 1110