

Portable Generators



Dependable jobsite power

Construction Starts Here



Portable Generators



Features available on all models except where noted.

Meet MultiQuip's newest generator models... the preferred generators of contractors everywhere!

- **Control Panel** — Rugged new look withstands the rough handling on the job site or in the back of a truck.
- **Receptacles** — Additional twist-lock receptacles have been added for operator convenience.
- **Lifting Bail** — Standard on 3.6 kW to 6 kW models. Hinged design lays flat when not in use.
- **Engines** — MultiQuip generators are now available with either Honda GX-Series or Robin EX-Series industrial grade engines.
- **Electric Start** — available on 6 kW models; standard on 9.7 kW model.
- **Brushless design** — low maintenance for years of dependable service.
- **Superior voltage regulation** — helps to keep tools and equipment running at optimal levels; helps them last longer.

Voltmeter

This feature serves as a convenient diagnostic tool on the jobsite. The operator can quickly tell whether or not the generator is producing the correct voltage and prevent overheating of expensive tools and equipment.



Silent Type Muffler

Reduces noise level on Honda units. USFS-approved spark arrestors standard on 2.5kW through 6kW Honda-powered models.

Reliability

GA-Series generators use a brushless design that minimizes maintenance by eliminating the carbon brushes and slip rings common on competitive models.

The best warranty in the industry.

All GA-Series generators are covered by a two-year parts and labor warranty.



There's a size and model for every application...



2500 watts max.
120V
Honda engine
Recoil start
GA-2.5H



2900 watts max.
120V
Robin engine
Recoil start
GA-2.9R



3600 watts max.
120/240V
Honda engine
Recoil start
GA-3.6HA



4500 watts max.
120/240V
Robin engine
Recoil start
GA-4.5RA



Portable Generators



Also available with
Recoil/Electric Start
as Model GA-6HEA

6000 watts max.
120/240V
Honda engine
Recoil start
GA-6HA



Also available with
Recoil Start as
Model GA-6RA

6000 watts max.
120/240V
Robin engine
Recoil/Electric start
GA-6REA



Unit shown on optional
WKT-97 Wheel Kit

9700 watts max.
120/240V
Honda engine
Recoil/Electric start
GA-9.7HE



UWK Wheel Kit
For 2.5kw through 6kw models;
Shown with handles in both up and
down positions.



Diesel Powered Generator

Delivers dependable performance for a variety of industrial and commercial applications.

Compact, sound-attenuated package with full instrumentation, including hour meter and warning lights for oil, water and battery.

- 7kW maximum, 6kW continuous
- Brushless alternator design
- 13.9 HP water-cooled Kubota diesel engine
- Quiet operation — 65.7 dBA @ 23 feet



Shown on optional TRLR10W trailer

7000 watts max.
 120/240V
 Kubota diesel engine
 Electric start
DA7000SSW

High Cycle Generator

Simultaneously produces both 60 and 180 Hz power

The only choice for dual-use portable power.

Simultaneously produces standard 60 Hz power and 180 Hz power for "high-cycle" concrete vibrators. No other high-cycle generator is this versatile.

- Produces 5000 watts of 120/240-volt 180-cycle power
- Produces 4000 watts 120/240-volt 60-cycle power
- Rugged control panel withstands rough handling
- Powers up to three Multiquip 2" high-cycle vibrators or two of our 2 5/8" vibrator heads (varies according to current requirements).
- Lifting bail standard — hinged design lays flat when not in use.
- Engine — powered by an 11 HP Honda GX-Series with low oil shutdown.
- Produces 5000 watts of 120/240-volt 180-cycle power
- Produces 4000 watts 120/240-volt 60-cycle power



5000 watts max.
 120/240V 180-cycle
4000 watts max.
 120/240V 60-cycle
 Honda gas engine
GDP-5H

Portable Generator Specifications

MODEL	GA-2.5H	GA2.9R	GA-3.6HA	GA-4.5RA	GA-6HA	GA-6HEA	GA-6RA	GA-6REA	GA-9.7HE	DA7000SSW
Alternator Design	Brushless									
Maximum Watts	2,500	2,900	3,600	4,500	6,000	6,000	6,000	6,000	9,700	7,000
Continuous Watts	2,200	2,600	3,200	3,700	5,000	5,000	5,000	5,000	8,400	6,000
Voltage	120V					120/240V				
Max. Amps @ 120V	20.8	24.2	30	37.5	50	50	50	50	80.8	58.3
Cont. Amps @ 120V	18.3	21.7	26.6	30.8	41.6	41.6	41.6	41.6	70	50
Max. Amps @ 240V	N/A	N/A	15	18.75	25	25	25	25	40.4	29.2
Cont. Amps @240V	N/A	N/A	13.3	15.4	20.8	20.8	20.8	20.8	35	25
Frequency/Phase	60 Hz / Single phase									
Voltmeter	Standard									
Full Power Switch	N/A					Standard				
RECEPTACLES* AND CIRCUIT BREAKERS										
5-20R 125V GRCI 20A	✓	✓	✓ (2)	✓ (2)	✓ (2)	✓ (2)	✓ (2)	✓ (2)	✓	✓ (2)
L5-20R 125V T-Lock 20A	✓	✓	✓	✓	✓	✓	✓	✓	✓	
L5-30R 125V T-Lock 30A			✓	✓	✓	✓	✓	✓	✓	✓
L6-20R 250V T-Lock 20A										✓
L14-20R 125/250V T-Lock 20A			✓	✓						
L14-30R 125/250V T-Lock 30A					✓	✓	✓	✓	✓	✓
CS-6369 125/250VAC 50A										✓
Main Circuit Breaker	20A	22A	13.5A	15A	21A	21A	21A	21A	35A	25A
Number of Poles	1					2				
ENGINE										
Engine Manufacturer	Honda	Robin	Honda	Robin	Honda	Honda	Robin	Robin	Honda	Kubota Diesel
Engine Model	GX-160	EX-17D	GX-240	EX-27D	GX-340	GX-340	EH-36	EH-36	GX-610	Z482
Horsepower (KW)	5.5 (4.1)	5.7 (4.2)	8.0 (6.0)	9.0 (6.7)	11.0 (8.25)	11.0 (8.25)	11.4 (8.5)	11.0 (8.25)	18.0 (13.5)	12.5 (9.3)
Rated Speed — RPM	3,600									
Low Oil Shutdown	Standard									
Starting Systems**	Recoil					Recoil/Elect.	Recoil	Recoil/Elect.		Electric
Fuel Capacity — gal (ltr)	3.2 (12)	2.6 (10)	5.0 (19)	5.0 (19)	5.0 (19)	5.0 (19)	5.0 (19)	5.0 (19)	10.0 (37.8)	12.5 (9.3)
Running Time — hr./tank***	6	5	5.5	5.5	5.5	5.5	5.5	5.5	6.75	10
Fuel Gauge	Standard									
Automatic Idle Control	N/A					Standard				
Sound Level dB@ 23 ft.	70	71	73	75	76	76	76	81	78	65.7
DIMENSIONS AND WEIGHT										
Length — in. (cm)	20 (50)	20 (50)	24.4 (61)	23 (58)	25.6 (64)	25.6 (64)	26.4 (64)	26.4 (64)	31.25 (79)	25 (64)
Width — in. (cm)	16.1 (40)	16 (40)	22 (56)	18.5 (46)	22.6 (58)	22.6 (58)	22.0 (56)	22.6 (57)	21.25 (54)	45 (114)
Height — in. (cm)	18.5 (46)	18 (44)	21.3 (54)	20.3 (51)	21.3 (54)	21.3 (54)	22.4 (57)	22.4 (57)	28 (71)	31 (79)
Dry Weight — lbs. (kg)	110 (50)	108 (49)	170 (77)	149 (68)	201 (91)	216 (98)	192 (87)	214 (97)	326 (148)	551 (250)
OPTIONS										
Wheel Kit	UWK								WKT-97	WKT225A
Trailer	N/A									TRLR10W‡

Your Multiquip dealer is:

Cessco Inc.

4222 NE Columbia Blvd.
Portland, OR 97218

WWW.CESSCO.US

esales@cessco.us

Commercial:

(503) 288-1242

Fax:

(503) 288-4284

Toll Free:

(800) 882-4959

* See receptacle charts inside brochure.

** Electric start models are shipped less battery.

*** All running times computed at full load using fuel consumption rates supplied by engine manufacturer.

‡ Requires adapter kit.

Note: Some units may be shown with optional equipment.



MULTIQUIP INC.

POST OFFICE BOX 6254

CARSON, CA 90749

310-537-3700 • 800-421-1244

FAX: 310-537-3927

E-MAIL: mq@multiquip.com

www.multiquip.com

All features and specifications are subject to change without notice.

MQGEN-9297 Rev. D (02-05)

Units manufactured by Denyo Mfg. Co.